



COSHH SAFETY DATA SHEET

CM STAYWHITE SILICONE SEALANTS

JANUARY 2016

1. Product and company identification.

Product name: CM STAYWHITE SILICONE SEALANT
Colours: White only

Supplier: CM SEALANTS
Kendon House
Selby Road
Leytonstone
London
E11 3LT
Telephone number 020 8519 6358
Fax 020 8555 0394

2. Composition/information on ingredients

PREPARATION

Chemical nature: Polydimethylsiloxanes, amorphous silica & crosslinker.
Components presenting hazards: Alkyltriacetoxysilanes (CAS: 4253-34-3 17689-77-9): <5% -EEC classification: C;R34.
Further information During use, acetic acid is released (CAS:64-19-7).

3. Hazards identification

MOST IMPORTANT HAZARDS

Adverse human health effects: Slightly irritating to eyes, respiratory system and skin.
Environmental effects: Presents no particular risk to the environment, provided the disposal requirements (see section 13) and national or local regulations are complied with.

Physical and chemical hazards:
Fire or explosion Combustible.
Further hazards On contact with humidity: irritating vapours are released.
Classification/Specific hazards: According to EEC criteria, this product is not classified as a "hazardous preparation".
Further information: After drying, may stick to the skin.



COSHH SAFETY DATA SHEET

CM STAYWHITE SILICONE SEALANT

4. First-aid measures

| | |
|--------------|--|
| Inhalation | Move to the fresh air. If irritation persists, consult a doctor. |
| Skin contact | Wipe off as much as possible (using a clean, soft, absorbent material). Wash immediately with plenty of soap and water. |
| Eye contact | Immediately rinse with water for a prolonged period whilst keeping the eyes wide open. If irritation persists, consult an eye specialist. |
| Ingestion | Consult a doctor if necessary. |

5. Fire-fighting measures

| | |
|---------------------------------|--|
| Extinguishing media Suitable | Carbon dioxide (CO ₂). Foam Powders Water spray |
| Not suitable | None to our knowledge. If there is a fire close by, use suitable extinguishing agents. |
| Specific hazards | Combustible. During combustion: Toxic and highly flammable gases are released (explosion hazard). Hazardous dust is released. |
| Specific fire fighting methods | Cool down the containers/equipment exposed to heat with a water spray. |
| Protection of fire-fighters | Self-contained breathing apparatus. |

6. Accidental release measures

| | |
|---------------------------|--|
| Personal precautions | Avoid contact with skin and eyes Do not breathe vapours. Protective equipment: For further information refer to section 8 "Exposure-controls/personal protection" Mechanically ventilate the spillage area. |
| Environmental precautions | This product does not present any particular risk for the environment. |
| Methods for cleaning up | |
| Recovery | Recover the product by scraping with a spatula or a similar instrument. Collect up the product and place it in a spare container: suitably labelled tightly closed |
| Neutralization | Absorb residues with: inert absorbent material |



COSHH SAFETY DATA SHEET

CM STAYWHITE SILICONE SEALANT

6. Accidental release measures con.

| | |
|--------------------------|--|
| Cleaning/Decontamination | Decontaminate and wash the floor with an appropriate self-emulsifying solvent Then wash with plenty of water. |
| Disposal | For disposal of solid materials refer to section 13 "Disposal considerations" |

7. Handling and storage

HANDLING

| | |
|----------------------|--|
| Technical measures | Ventilation |
| Measures | Do not exceed the occupational exposure limits (OEL) |
| Safe handling advice | Comply with instructions for use (refer to technical sheet). Work outside or in a well-ventilated room. |

STORAGE

| | |
|-----------------------|--|
| Technical measures | Does not require any specific or particular technical measures. |
| Storage conditions | |
| Recommended | Keep: only in the original container the container tightly closed and dry. Strong oxidizing agents. |
| Incompatible products | |
| Packaging | Polyethylene liner in a metal drum varnished with epikote. Polyethylene cartridges 9outer packaging – cardboard box). |
| Packaging materials | |
| Recommended | Polyethylene. Coated metals. |
| Further information | The product polymerises on contact with air. |

8. Exposure controls/personal protection

| | |
|------------------------------|--|
| Engineering measures | Ensure good ventilation of the workstation. |
| Occupational exposure limits | |
| Limits (France) | Acetic acid: VLE: 25mg/m ³ (10 ppm). |
| Limits (USA/ACGIH) | Acetic acid: TLV (TWA) = 25mg/m ³ (10 ppm). Acetic acid: TLV (STEL) = 37mg/m ³ (15 ppm). |
| Limits (UK) | Acetic acid: OES: 10 ppm or 25mg/m ³ – (Long term exposure limit – 8h TWA reference period) OES: 15 ppm or 37mg/m ³ (Short term exposure limit – 15 minute reference period) |



COSHH SAFETY DATA SHEET

CM STAYWHITE SILICONE SEALANT

8. Exposure controls/personal protection con.

| | |
|--------------------------------|---|
| Surveillance procedures | Measure the concentration in the atmosphere. |
| Personal protective equipment | |
| Respirator protection | In the event of insufficient ventilation: Respiratory protective device with a gas filter. |
| Hand Protection | Protective gloves made of rubber. |
| Eye protection | Safety spectacles. |
| Collective emergency equipment | Eye fountain. |

9. Physical and chemical properties

APPEARANCE

| | |
|------------------------------|--|
| Physical state | Thixotropic paste. |
| Colour | Translucent or pigmented |
| Odour | of vinegar. |
| pH | Not applicable |
| Specific temperatures | |
| Decomposition temperature | >200 C |
| Flammability characteristics | |
| Flash point | >150 C (Closed cup, according to method Afnor T 60103). |
| Oxidizing properties | Non-oxidizing material according to EEC criteria. |
| Specific gravity | Approx. 1040 kg/m ³ at 25 C |
| Solubility | |
| in water | Practically insoluble. |
| in organic solvents | Insoluble in: acetone alcohol (ethanol) Dispersible (partial solubilisation) in: petrol white spirit aromatic hydrocarbons (toluene, xylene). chlorinated solvents. |



COSHH SAFETY DATA SHEET

CM STAYWHITE SILICONE SEALANT

10. Stability and reactivity.

| | |
|----------------------------------|---|
| Stability | Stable at room temperature provided it is not on contact with air. Vulcanises at room temperature on contact with moisture in the air. |
| Hazardous reactions | |
| Conditions to avoid | No dangerous reactions known under normal conditions of use. See technical data sheet. |
| Hazardous decomposition products | During vulcanisation, acetic acid is released. (Quantity potentially released: 2.4% of product weight). On combustion forms: (Carbon oxides (CO + CO ₂)). (Silica). |

11. Toxicological information

| | |
|----------------|--|
| Acute toxicity | (Acetic acid). LC 50 inhalation (Mouse)/1 h: 14mg/l. (Published data). |
| Local effects | At high concentrations, the vapours can be irritating to the respiratory system. Repeated or prolonged contact may cause slight irritation to the skin. May cause light temporary irritation to ocular mucous membranes. |

12. Ecological information

| | |
|------------------------------------|---|
| MOBILITY | |
| Precipitation | Slightly soluble product, readily forms deposits. |
| Expected behaviour of the product | Ultimate destination of the product: SOIL and SEDIMENT. |
| BIODEGRADABILITY | |
| Ultimate aerobic biodegradability | Not biodegradable. |
| BIOACCUMULATION | |
| Bioconcentration factor | Not bioaccumulable. |
| ECOTOXICITY | |
| Effects on the aquatic environment | Acetic acid EC 50 (Daphnia: Daphnia magna)/24 h: 150 mg/l. LC 50 (Fish: Pimephales promelas)/96 h: 88 mg/l. |



COSHH SAFETY DATA SHEET

CM STAYWHITE SILICONE SEALANT

13. Disposal considerations

WASTE FROM RESIDUES

Destruction/Disposal Dispose of at a licensed waste collection point.

CONTAMINATED PACKAGING

Decontamination/cleaning Separate the different packaging components and treat them separately:

Destruction/Disposal Incinerate plastic packaging at a licensed installation.

Entrust the uncontaminated packaging to a licensed waste contractor.

Following decontamination, re-use or recycle metal packaging.

Disposable containers:

Incinerate at a licensed installation.

NOTE: The users attention is drawn to the possible existence of local regulations regarding disposal.

14. Transport information

INTERNATIONAL REGULATIONS

Land

Rail/road (RID/ADR) NOT restricted.

Sea (IMO/IMDG) NOT restricted.

Air (ICAO-IATA) NOT restricted.

NOTE: The above regulatory prescriptions are those valid on the date of publication of this sheet.
given the possible evolution of transport regulations for hazardous materials, it would be advisable to check their validity with your sales office.

15. Regulatory information

LABELLING

EEC regulations Mandatory labelling (self-classification) of hazardous preparations:
Not applicable.

Further regulations

United Kingdom Handle in accordance with relevant British legislation:
Control of Substances Hazardous to Health Regulations
Environmental Hygiene Guidance: EH/40 Occupational Exposure Limits (revised annually).

NOTE: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the Safety Data Sheet. The users attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.



COSHH SAFETY DATA SHEET

CM STAYWHITE SILICONE SEALANT

16. Other information

Uses

Recommended uses

Used for making joints, sealing and gluing.
(For further information, refer to the product technical data sheet)

Prohibited uses

this product is only intended for industrial use.

European inventory (EINECS,ELINCS)

These polymers are not concerned by the EINECS inventory.
The corresponding monomers are registered in the EINECS inventory.
All the other constituents of this preparation are registered in the EINECS inventory.

American inventory (TSCA)

All the components of this preparation are registered in the TSCA inventory.

This safety data sheet should be used in conjunction with technical sheets. It does not replace them. The information given is based on our knowledge of this product, at the time of publication. It is given in good faith. The attention of the user is drawn to the possible risks incurred by using the product for any other purpose other than that for which it was intended. This does not in any way excuse the user from knowing and applying all the regulations governing his activity. It is the sole responsibility of the user to take all precautions required in handling the product. The aim of the mandatory regulations mentioned is to help the user to fulfil his obligations regarding the use of hazardous products. This information is not exhaustive. This does not exonerate the user from ensuring that legal obligation, other than those mentioned, relating to the use and storage of the product, do not exist. This is solely his responsibility.

CM Sealants
Selby Road
Leytonstone
London
E11 3LT

020 8519 6358
[**info@cmsealants.co.uk**](mailto:info@cmsealants.co.uk)

